

产品名称: 开关矩阵



型号 Model Number	频率范围 Frequency Range(GHz)	驻波比 VSWR	插入损耗 Insertion Loss(dB)	输入端功率 Input Power(dBm)	切换速率 Switch Speed	隔离度 Isolation (dB)	连接器形式 Connector Type	外形尺寸 Dimension (mm)	重量 Weight (kg)
SHX-GKTS-SPS1/6-0/4-SMA(K)	DC-6	≤1.2	≤0.2	47	≤15ms	≥80	SMA(K)	236×302×113.5	2.5
SHX-GKTS-PSP1/6-0.8/2.5-SMAK	0.8-2.5	≤1.5	≤1.5	40	≤15ms	≥50	SMA(K)	236×302×113.5	3
SHX-GKTS-PSP1/8-15-SMAK	DC-15	≤1.5	≤1.5	40	≤15ms	≥50	SMA(K)	302×236×113.5	2
SHX-GKTS-SPS1/16-0.8/2.5-SMAK	0.8-2.5	≤1.6	≤4.0	40	≤20ms	≥60	SMA(K)	342×361×147.5	5.3
SHX-GKTS-SPS2×4-8-SMA(K)	DC-8	≤1.6	≤1.5	40	≤15ms	≥80	SMA(K)	236×302×113.5	3
SHX-GKTS-SPS3×6-6-SMA(K)	DC-6	≤1.6	≤1.4	40	≤20ms	≥75	SMA(K)	342×361×147.5	3.5
SHX-GKTS-MSP6/6-18-SMAK	DC-18	≤1.5	≤1.5	40	≤15ms	≥50	SMA(K)	302×236×113.5	2
SHX-GKTS-PSS8x4-0.8/3.0-NK	0.8-3.0	≤1.6	≤16	40	≤15ms	≥75	N(K)	483×478×177	12
SHX-GKTS-PSS8/16-0.8/2.5-NK	0.8-2.5	≤1.5	≤17	33	≤15ms	/	N(K)	483×532×513	25
SHX-GKTS-SPS12x12-1.8/2.7-NK-L	1.8-2.7	≤1.6	≤28	40	≤15us	≥90	N(K)	483×310×570	30
SHX-GKTS-PSS24/8-0.8/2.5-NK	0.8-2.5	≤1.5	≤20	40	≤10ms	≥40	N(K)	483×532×562	26