

型号 2路高频功分器



型号	工作频段 (GHz)	驻波比	插入损耗(dB)	幅度平衡(dB)	相位平衡(°)	平均功率(W)	隔离度 (dB)	连接器形式	外形尺寸 L×W×H(mm)
SHX202-003180	0.3-18	1.5	≤2.8	≤0.4	±5°	20	≥17(0.3-1) ≥20(1-18)	SMA(F)	292.1×44.5×12.7
SHX202-004265	0.4-26.5	1.5	≤1.9	≤0.3	±4°	20	≥16(0.4-1) ≥20(1-26.5)	SMA(F)	149.1×26.4×12.7
SHX202-005080	0.5-8	1.4	≤1.0	≤0.2	±3°	20	≥17(0.5-1) ≥20(1-8)	SMA(F)	149.1×26.4×12.7
SHX202-005180	0.5-18	1.4	≤1.5	≤0.3	±4°	20	≥17(0.5-1) ≥20(1-18)	SMA(F)	149.1×26.4×12.7
SHX202-005265	0.5-26.5	1.5	≤1.9	≤0.4	±4°	20	≥17(0.5-1) ≥20(1-26.5)	SMA(F)	149.1×26.4×12.7
SHX202-005400	0.5-40	1.6	≤3.5	≤0.5	±6°	20	≥17(0.5-1) ≥20(1-40)	2.92(F)	149.1×26.4×12.7
SHX202-010180	1-18	1.4	≤1.2	≤0.3	±3°	20	≥17(1-1.5) ≥20(1.5-18)	SMA(F)	95.3×26.4×12.7
SHX202-010265	1-26.5	1.5	≤1.6	≤0.3	±4°	20	≥17(1-1.5) ≥20(1.5-26.5)	SMA(F)	95.3×26.4×12.7
SHX202-010400	1-40	1.6	≤3.0	≤0.5	±6°	20	≥17(1-1.5) ≥20(1.5-40)	2.92(F)	95.3×26.4×12.7
SHX202-020180	2-18	1.4	≤1.0	≤0.3	±3°	20	≥18(2-2.5) ≥20(2.5-18)	SMA(F)	45.5×26.4×12.7
SHX202-020265	2-26.5	1.6	≤1.2	≤0.3	±4°	20	≥18(2-2.5) ≥20(2.5-26.5)	SMA(F)	45.5×26.4×12.7
SHX202-020400	2-40	1.6	≤1.8	≤0.3	±4°	20	≥18(2-2.5) ≥20(2.5-40)	2.92(F)	45.5×26.4×12.7
SHX202-060180	6-18	1.4	≤0.8	≤0.2	±3°	20	≥18	SMA(F)	29.2×26.9×12.7
SHX202-060265	6-26.5	1.5	≤1.2	≤0.3	±4°	20	≥18	SMA(F)	29.2×26.9×12.7
SHX202-060400	6-40	1.6	≤1.5	≤0.3	±5°	20	≥18	2.92(F)	29.2×26.9×12.7
SHX202-100265	10-26.5	1.5	≤1.2	≤0.3	±4°	20	≥20	SMA(F)	29.2×26.9×12.7
SHX202-100400	10-40	1.6	≤1.5	≤0.3	±5°	20	≥20	2.92(F)	29.2×26.9×12.7
SHX202-180265	18-26.5	1.5	≤1.2	≤0.3	±3°	20	≥20	SMA(F)	22×26.9×12.7
SHX202-180400	18-40	1.6	≤1.5	≤0.3	±4°	20	≥20	2.92(F)	22×26.9×12.7

标称阻抗: 50Ω

备注:

1. 所有外形尺寸单位 mm, 尺寸公差±2%