

型号 4 路高频功分器



型号	工作频段 (GHz)	驻波比	插入损耗(dB)	幅度平衡(dB)	相位平衡(°)	平均功率(W)	隔离度 (dB)	连接器形式	外形尺寸 L×W×H(mm)
SHX204-003180	0.3-18	1.5	≤7.5	≤±0.4	±4°	20	≥18	SMA(F)	335.3×71.1×12.7
SHX204-003265	0.3-26.5	1.5	≤11	≤±0.5	±6°	20	≥18	SMA(F)	335.3×71.1×12.7
SHX204-004080	0.4-8	1.5	≤2.0	≤±0.4	±4°	20	≥16(0.4-1) ≥20(1-8)	SMA(F)	158.5×75×12.7
SHX204-004180	0.4-18	1.6	≤4.0	≤±0.5	±6°	20	≥16(0.4-1) ≥20(1-18)	SMA(F)	158.5×75×12.7
SHX204-004265	0.4-26.5	1.65	≤5.4	≤±0.5	±7°	20	≥16(0.4-1) ≥20(1-26.5)	SMA(F)	158.5×75×12.7
SHX204-005080	0.5-8	1.5	≤2.0	≤±0.4	±4°	20	≥16(0.5-1) ≥20(1-8)	SMA(F)	158.5×75×12.7
SHX205-005180	0.5-18	1.6	≤3.8	≤±0.3	±5°	20	≥16(0.5-1) ≥20(1-18)	SMA(F)	158.5×75×12.7
SHX204-005265	0.5-26.5	1.6	≤5.2	≤±0.4	±6°	20	≥16(0.5-1) ≥20(1-26.5)	SMA(F)	158.5×75×12.7
SHX204-005400	0.5-40	1.7	≤7.5	≤±0.5	±8°	20	≥16(0.5-1) ≥20(1-40)	2.92(F)	158.5×75×12.7
SHX204-010180	1-18	1.5	≤2.5	≤±0.4	±5°	20	≥17	SMA(F)	132.1×51.8×12.7
SHX204-010265	1-26.5	1.6	≤2.8	≤±0.5	±6°	20	≥17	SMA(F)	132.1×51.8×12.7
SHX204-010400	1-40	1.7	≤5.0	≤±0.6	±7°	20	≥17	2.92(F)	132.1×51.8×12.7
SHX244-020180	2-18	1.5	≤2.0	≤±0.5	±6°	20	≥16	SMA(F)	78.7×51.6×12.7
SHX204-020180	2-18	1.5	≤2.4	≤±0.3	±4°	20	≥18	SMA(F)	78.7×51.6×12.7
SHX204-020265	2-26.5	1.6	≤2.7	≤±0.4	±5°	20	≥18	SMA(F)	78.7×51.6×12.7
SHX204-020400	2-40	1.7	≤4.5	≤±0.5	±7°	20	≥18	2.92(F)	78.7×51.6×12.7
SHX204-060265	6-26.5	1.6	≤1.9	≤±0.3	±3°	20	≥16	SMA(F)	38.1×70×12.7
SHX204-060400	6-40	1.65	≤2.5	≤±0.4	±5°	20	≥16	2.92(F)	38.1×70×12.7
SHX204-100265	10-26.5	1.6	≤1.9	≤±0.3	±3°	20	≥18	SMA(F)	38.1×70×12.7
SHX204-100400	10-40	1.65	≤2.5	≤±0.4	±5°	20	≥18	2.92(F)	38.1×70×12.7
SHX204-180265	18-26.5	1.6	≤1.7	≤±0.3	±3°	20	≥19	SMA(F)	38.1×52.3×12.7
SHX204-180400	18-40	1.7	≤2.3	≤±0.4	±5°	20	≥18	2.92(F)	38.1×52.3×12.7

标称阻抗: 50Ω

备注:

1. 所有外形尺寸单位 mm, 尺寸公差±2%