



1/2 波纹管



RG142



RG223



RG316



SR141



SF141



SS141



RG393



MR400



SHX210



RG179



RG6

产品名称	接头形式	外径	最小弯曲半径	特性阻抗	插入损耗						最大驻波比	
					1G	3G	6G	10G	18G	27G		40G
1/2 波纹管	N,L29	Ø13.4	125	50Ω		≤0.7						≤1.20
RG142	N,SMA,BNC	Ø4.95	25	50Ω		≤1.0						≤1.20
RG223	N,SMA,BNC	Ø5.3	25	50Ω		≤1.0						≤1.20
RG316	N,SMA,BNC	Ø2.52	13	50Ω		≤1.6						≤1.20
SR141	N,SMA,BNC	Ø3.58	13	50Ω				≤1.4				≤1.20
SF141	N,SMA,BNC	Ø3.58	40	50Ω			≤1.1					≤1.20
SS141	N,SMA	Ø5.15	25	50Ω			≤1.2					≤1.20
RG393	N,L29	Ø9.91	51	50Ω		≤0.5						≤1.20
MR400	N,L29,TNC	Ø10.3	100	50Ω		≤0.4						≤1.20
SHX210	N,SMA	Ø5.5	50	50Ω				≤1.5				≤1.25
SHX3450	N,SMA	Ø7.4	26	50Ω						≤1.1		≤1.20
SHX3449	2.4,2.92	Ø4.8	26	50Ω							≤3.8	≤1.20
RG179	F	Ø2.54	10	75Ω	≤0.9							≤1.20
RG6	N,BNC	Ø7.07	70	75Ω	≤0.5							≤1.25

备注:

1. 所有外形尺寸单位 mm, 尺寸公差±5%
2. 可按照客户要求订制特殊规格接头和长度